



WASH HAND BASIN			
CODE	SPECIFICATION	COLOR	IMAGE
BASW05	REMOVE EXISTING WASH HAND BASIN REPLACE WITH NEW VAAL SANITARYWARE MIDI-WEAVER BASIN (CODE 706601) WITH 20mm CHROME PLATED SINGLE BASIN MIXER RESTRICTED TO 60mm MAXIMUM FLOW (CODE KO-951) ALLOW FOR ALL OTHER FITTINGS TO REPLACE THE WHB INCLUDING FLEXIBLE PIPES, TRAP ETC. AND CONNECTING TO EXISTING SERVICES. DEEMED TO COMPLY TO SPECIFICATIONS: CERAMIC WHB 497	WHITE	

PARAPLEGIC TOILET			
CODE	SPECIFICATION	COLOUR	IMAGE
844820	<p>Vaal Sanitaryware vitreous china "Pearl Paraplegic" semi-close coupled 90° outlet open rim washdown pan and matching 9 litre cistern complete with lid, fittings, and purpose made C.P. side-flush lever (left or right). Supplied with purpose made thermostat seat and cover plate. The suite is designed to flush effectively on 6 litres.</p> <p><b>SPECIFICATIONS</b>            Mass Volume            Pan 14.00kg 0.075m³            Cistern 12.00kg 0.030m³</p> <p><b>ADDITIONAL REQUIREMENTS</b>            1.Vaal Sanitaryware Hibiscus basin.            2.2x12 mm C.P. lever action pillar taps.            3.Universal Half Pedestal (code 715222).            4.32 mm stainless steel side grab rail (code D12).            5.32 mm stainless steel rear grab rail around cistern (code SR2A).</p>	WHITE	

WATER CLOSETS			
CODE	SPECIFICATION	COLOR	IMAGE
BASW02	<p>REMOVE EXISTING WC FITTING, REPLACE WITH NEW VAAL SANITARYWARE FLATBACK VITREOUS CHINA CLOSE COUPLE SUITE (CODE 773662) COMPRISING 90° OUTLET CLOSED RIM WASH-DOWN PAN WITH MATCHING BLITRE CISTERN INCLUDING FITMENT AND THERMOSET SOFT CLOSED SEAT.</p> <p>NOTE: ALLOW FOR ALL OTHER FITTINGS TO REPLACE THE WC INCLUDING FLEXIBLE PIPES, PAN, SEALER ETC TO CONNECT TO EXISTING SERVICES. DEEM TO COMPLY TO SPECIFICATION: CERAMIC WHB TO SANS497</p>	WHITE	

FINISHES SCHEDULE		
CODE	SPECIFICATION	COLOR
BBF01	SERIE ROCK 636 DARK GREY MATT PORCELAIN TILES COMPLYING WITH SANS 1449/13006 FIXED TO PREPARED FLOOR SCREED WITH APPROVED TILE ADHESIVE MIXED WITH BONDING LIQUID IN LIEU OF WATER. JOINTS TO BE GROUTED WITH TILE GROUT WITH MINIMUM 5mm EXPANSION JOINTS AT PERIMETRE. ALL STRUCTURAL EXPANSION AND CONSTRUCTION JOINTS at MAXIMUM OF 5m CENTRES IN BOTH DIRECTIONS. ALL SPECIFICATIONS TO MANUFACTURERS REQUIREMENTS.	DARK GREY
WALLS		
CODE	SPECIFICATION	COLOR
BAW01	SERIE ROCK 636 LIGHT GREY MATT PORCELAIN TILES COMPLYING WITH SANS 1449/13006 FIXED TO PREPARED WALL SCREED WITH APPROVED TILE ADHESIVE MIXED WITH BONDING LIQUID IN LIEU OF WATER. JOINTS TO BE GROUTED WITH TILE GROUT WITH MINIMUM 5mm EXPANSION JOINTS AT PERIMETRE. ALL STRUCTURAL EXPANSION AND CONSTRUCTION JOINTS at MAXIMUM OF 5m CENTRES IN BOTH DIRECTIONS. ALL SPECIFICATIONS TO MANUFACTURERS REQUIREMENTS.	LIGHT GREY
BAWM01	DOUGLAS JONES 435-48x48mm MESH BACKED CERAMIC MOSAICES INSTALLED AS VANITY SPLASHBACK. (3 MOSAIC TILES HIGH) FIXED MESH DOWN TO INTERNAL PLASTERED WALL. FIX ADHESIVE MIXED WITH BONDING LIQUID IN LIEU OF WATER. LAID WITH TILE GROUT, APPLIED WITH FLEXIBLE SPATULA. EXCESS GROUT REMOVED WITH DAMP SPONGE. TILES TO BE WASHED WITH GLINT TILE CLEANER ONCE GROUT HAS CURED.	DARK GREY
BAWM01	PLASCON Y5-E2-3. ABOVE WALL TIELS, UP TO THE CEILING LEVEL. PREPARE WALL, REMOVE ALL RESIDUE, FLAKING AND DUST, MAKE GOOD WITH POLYFILLA OR RHINOLITE, TO RECEIVE 1 COAT UNIVERSAL UNDERCOAT AND 2 COATS OF PLASCON DOUBLE VELVET WALL PAINT.	AMAZON MIST

FINISHES SCHEDULE		
CODE	SPECIFICATION	COLOR
BBF01	SERIE ROCK 636 DARK GREY MATT PORCELAIN TILES COMPLYING WITH SANS 1449/13006 FIXED TO PREPARED FLOOR SCREED WITH APPROVED TILE ADHESIVE MIXED WITH BONDING LIQUID IN LIEU OF WATER. JOINTS TO BE GROUTED WITH TILE GROUT WITH MINIMUM 5mm EXPANSION JOINTS AT PERIMETRE. ALL STRUCTURAL EXPANSION AND CONSTRUCTION JOINTS at MAXIMUM OF 5m CENTRES IN BOTH DIRECTIONS. ALL SPECIFICATIONS TO MANUFACTURERS REQUIREMENTS.	DARK GREY
WALLS		
CODE	SPECIFICATION	COLOR
BAW01	SERIE ROCK 636 LIGHT GREY MATT PORCELAIN TILES COMPLYING WITH SANS 1449/13006 FIXED TO PREPARED WALL SCREED WITH APPROVED TILE ADHESIVE MIXED WITH BONDING LIQUID IN LIEU OF WATER. JOINTS TO BE GROUTED WITH TILE GROUT WITH MINIMUM 5mm EXPANSION JOINTS AT PERIMETRE. ALL STRUCTURAL EXPANSION AND CONSTRUCTION JOINTS at MAXIMUM OF 5m CENTRES IN BOTH DIRECTIONS. ALL SPECIFICATIONS TO MANUFACTURERS REQUIREMENTS.	LIGHT GREY
BAWM01	DOUGLAS JONES 435-48x48mm MESH BACKED CERAMIC MOSAICES INSTALLED AS VANITY SPLASHBACK. (3 MOSAIC TILES HIGH) FIXED MESH DOWN TO INTERNAL PLASTERED WALL. FIX ADHESIVE MIXED WITH BONDING LIQUID IN LIEU OF WATER. LAID WITH TILE GROUT, APPLIED WITH FLEXIBLE SPATULA. EXCESS GROUT REMOVED WITH DAMP SPONGE. TILES TO BE WASHED WITH GLINT TILE CLEANER ONCE GROUT HAS CURED.	DARK GREY

Rev.	Date	Description of Revision	Prepared by	Checked by
1	01.03.18	FOR CONSTRUCTION		ND



Project Description:	
<b>BUILDING 8 BATHROOMS RENOVATIONS</b>	
Scale:	Date:
1:25 / A0	01/03/2018

Document Title:  
**BUILDING 8 BATHROOMS RENOVATIONS**

Drawing Number:	Page:	Revision:
<b>8FP3</b>	1/1	1
	Page Size:	
	A1	