

CODE	SPECIFICATION	COLOR
BBF01	SERIE ROCK 636 DARK GREY MATT PORCELAIN TILES COMPLYING WITH SANS 1449/13006 FIXED TO PREPARED FLOOR SCREED WITH APPROVED TILE ADHESIVE MIXED WITH BONDING LIQUID IN LIEU OF WATER. JOINTS TO BE GROUTED WITH TILE GROUT WITH MINIMUM 5mm EXPANSION JOINTS AT PERIMETRE. ALL STRUCTURAL EXPANSION AND CONSTRUCTION JOINTS at MAXIMUM OF 5m CENTRES IN BOTH DIRECTIONS. ALL SPECIFICATIONS TO MANUFACTURERS REQUIREMENTS.	DARK GRE
WALLS		
CODE	SPECIFICATION	COLOR
BAW01	SERIE ROCK 636 LIGHT GREY MATT PORCELAIN TILES COMPLYING WITH SANS 1449/13006 FIXED TO PREPARED WALL SCREED WITH APPROVED TILE ADHESIVE MIXED WITH BONDING LIQUID IN LIEU OF WATER. JOINTS TO BE GROUTED WITH TILE GROUT WITH MINIMUM 5mm EXPANSION JOINTS AT PERIMETRE. ALL STRUCTURAL EXPANSION AND CONSTRUCTION JOINTS at MAXIMUM OF 5m CENTRES IN BOTH DIRECTIONS. ALL SPECIFICATIONS TO MANUFACTURERS REQUIREMENTS.	LIGHT GRE
	150X900mm STONEBOX BLACK INK (ITALCOTTO) TILES COMPLYING WITH SANS 1449/13006 FIXED TO PREPARED WALL SCREED WITH APPROVED TILE ADHESIVE MIXED WITH BONDING LIQUID IN LIEU OF WATER. JOINTS TO BE GROUTED WITH TILE GROUT WITH MINIMUM 5mm EXPANSION JOINTS AT PERIMETRE. ALL STRUCTURAL EXPANSION AND CONSTRUCTION JOINTS at MAXIMUM OF 5m CENTRES IN BOTH DIRECTIONS. ALL SPECIFICATIONS TO COMPLY WITH MANUFACTURERS REQUIREMENTS.	DARK GRE
	PLASCON Y5-E2-3. ABOVE WALL TIELS, UP TO THE CEILING LEVEL. PREPARE WALL, REMOVE ALL RESIDUE, FLAKING AND DUST, MAKE GOOD WITH POLYFILLA OR RHINOLITE, TO RECEIVE 1 COAT UNIVERSAL UNDERCOAT AND 2 COATS OF PLASCON DOUBLE VELVET WALL PAINT.	AMAZON MIST
DOORS		
D1	PREPARE INTERIOR SIDE OF THE DOOR, REMOVE ALL RESIDUES, FLAKING AND DUST. MAKE GOOD WITH SMOOTH SAND PAPER AND WOOD FILLER TO RECEIVE 1 UNDERCOAT AND 2 COATS OF PLASCON WASHABLE DOUBLE VELVET PAINT. COLOR TO BE APPROVED BY THE PROJECT MANAGER PRIOR TO APPLICATION.	PANTONE 382
VANITY		
CODE	SPECIFICATION	COLOR
BAVS01	30mm THICK GRANITE TOP WITH 45° MITREDJOINT:2-3mm BEVEL ON SURFACE EDGE, FIXED TO SUPPORT USING DAB OF 100% CLEAR SILICONE ADHESIVE AT 200-300mm CENTRES ALONG SUPPORT JOINTS FILLED WITH MATCHING POLYSTER RESIN GLUE. SURFACE TO BE SEALED WITH AN APPROVED STONE SEALER. ALL IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.	WHITE
MIRROR		
CODE	SPECIFICATION	COLOR
BA01	GSA SMART GLASS IMAGES SILVERED FLOATGLASS COPPER-FREE MIRROR FIXED WITH CAPPED SCREW DIRECTLY ONTO THE WALL, 1250mm HIGH AND AS WIDE AS VANITY. DEEMED TO COMPLY WITH	SILVER BACKED

SPECIFICATION: GLAZED MIRROR IN ACCORDANCE TO NBR SCHEDULE1

AND SABS 0137.

UNDERSIDE OF SLAB	GENERAL		
	COPYRIGHT OF THIS DRAWING AND ITS CONTENTS IS HELD BY CSIR FACILITIES MANAGEMENT: PROJECTS SECTION		
	ALL DIMENSIONS AND LEVELS TO B SITE BY THE CONTRACTOR, AND AL	L	
	DISCREPANCIES REPORTED TO THI IMMEDIATELY.	E PROJECT MANAGER	
S			
NDERSIDE OF SLAB			
OF SLAB			
1			
ck Ink (Accent tile)			
	101.08.18FOR TENDERRev.DateDescription of Revision	ND Prepared by Signature	
	Client:		
		CSIR Facilities Building 35 627 Meiring Naudé Road	
		Pretoria	
	our future through se		
	Project Description:		
	CSIR BATH RENOVATION		
	Scale: 1:25/ A0	Date: 01/03/2018	
	Document Title:	I	
	BUILDING 33 S233		
	RENOVATIONS PF	ROJECT	
	Drawing Number:	Page: Revision:	
	33FP3	1/1 Page Size:	
		AO	